
















	Standard	Result
 Size	ISO 24342	1500.0mm x 230.0mm
 Thickness	ISO 24346	4.5mm
 Wear layer	ISO 24340	0.55 mm
Surface treatment		PU coating
Format		Gluedown
Warranty ¹	Commercial	15 years wear
	Domestic	35 years wear
 Bevelled edge		Micro
 Standards	ISO 10582	Pass
 Classification	ISO 10874 - Commercial	33: Commercial heavy
	ISO 10874 - Domestic	23: Domestic heavy
 Reaction to fire	AS/NZ ISO 9239.1:2003	CRF: 10.5 kW/m ² Smoke value: 60% min.
 Abrasion resistance	ISO 10582	Type 1
 Dimensional stability	ISO 23999	Pass (≤ 0.25%)
 Acoustic impact noise reduction	ISO 140-8 Improved Impact Sound Insulation	ΔL _w = 7 dB
 Indentation - residual	ISO 24343-1	Pass (≤ 0.1 mm) Avg result 0.06mm
 Castor chair continuous use	ISO 4918	Pass
 Slip resistance ²	AS/NZS 4586:2013	Suitable for underfloor heating. Max 27°C See separate table
 Adhesive	General use:	Kardean Mega-Bond
	High temperature:	Two-part chemical cure adhesive or, One-part modified silane heat and moisture resistant adhesive
Environmental	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.
	ISO 14001 / ISO 9001	Manufactured to quality and environment management systems standards
 Recycling		Suitable

¹ Subject to terms. Please see our website.

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

Please verify the current certification status with your Business Manager

For more information:

Call: 1800 33 11 70
Email: customerservice@pavimentoflooring.com.au
Visit: www.pavimentoflooring.com

Sep 25



	Product Code	Size		Box Quantity		Slip Resistance
		mm	inches	m ²	Pieces	
Wood Designs	PAV-AV001	1500.0 x 230.0	59.06 x 9.06	2.070	6 Planks	P3 /R10
	PAV-AV002	1500.0 x 230.0	59.06 x 9.06	2.070	6 Planks	P3 /R10
	PAV-AV003	1500.0 x 230.0	59.06 x 9.06	2.070	6 Planks	P3 /R10
	PAV-AV004	1500.0 x 230.0	59.06 x 9.06	2.070	6 Planks	P3 /R10
	PAV-AV005	1500.0 x 230.0	59.06 x 9.06	2.070	6 Planks	P3 /R10
	PAV-AV006	1500.0 x 230.0	59.06 x 9.06	2.070	6 Planks	P3 /R10
	PAV-AV007	1500.0 x 230.0	59.06 x 9.06	2.070	6 Planks	P3 /R10
	PAV-AV008	1500.0 x 230.0	59.06 x 9.06	2.070	6 Planks	P3 /R10