
Nature's Oak


HERRINGBONE
Valid from: 06:2025
Subject to change without notification

TECHNICAL DATA SHEET

PRODUCT SPECIFICATION	
Width	145mm
Length	580mm
Pack Size	1.009m^2
Planks per Pack	12 Planks
Pack Weight	9.48kg
Total Thickness	±14mm nominal
Surface Coating	High Performance UV Cured Acrylic Lacquer
Surface Treatment	Brushed Matt Finish

PHYSICAL PROPERTY	TEST METHOD	NATURE'S OAK HERRINGBONE
Construction		3 layers
Top Layer		2.5mm nominal
Colours in Range		4 designs
Edge Detail		No bevel
Grading	Internal (Vibrant)	Unlimited knots ≤ 80mm (EN1310)
Colour Variation		High
Installation Method		Glue down
Joining System		Tongue & grove
Moisture Content		6% - 8% MC
Slip Resistance	AS 4586:2013	P3
Abrasion Group	DIN 68861	>550
Fire Resistance	ASISO 9239.1-2003	4.6 Kw/m2 Smoke 13%
Thermal Resistance		R = 0.147
Electric Behavior		Static free
Indoor Air Quality - VOC	EN 717.1 / ISO16000	=.02mg/m^3 (<0.124mg/m^3) E1 large chamber
Warranty	Domestic Use Commercial Use	20 year wear and lifetime structural* Available upon request*





***Warranty Details**
Nature's Oak Flooring Warranty Terms and Conditions are available online at www.premiumfloors.com.au (in Australia) or www.floorscape.co.nz (in New Zealand) or from an authorised Nature's Oak Retailer.

Premium Floors Australia Pty Ltd – 3/35 – 45 Bend Road, Keysborough VIC 3175
Floorscape Ltd – Unit C, 19 Triton Drive, Rosedale Auckland 0632 New Zealand
Email: services.australia@unilin.com T +61 02 9982 3441
Email: sales.floorscape@floorscape.co.nz T +64 9 476 0428