| | | STANDARD | RESULT |
|---|---|---|---|
| | Size | ISO 24342 | **See page 2** |
| | Thickness | ISO 24346 | **4.5mm** |
| | Wear layer | ISO 24340 | **0.55 mm** |
| | Surface treatment | | **PU coating** |
| | Format | | **Gluedown** |
| | Warranty[1] | Commercial | **15 years wear** |
| | | Domestic | **35 years wear** |
| | Bevelled edge | | **Micro** |
| | Standards | ISO 10582 | **Pass** |
| | Classification | ISO 10874 - Commercial | **33: Commercial heavy** |
| | | ISO 10874 - Domestic | **23: Domestic heavy** |
| Bfl-s1 | Reaction to fire | AS/NZ ISO 9239.1:2003 | **CRF: 10.5 kW/m²** |
| | | | **Smoke value: 60% min.** |
| | Abrasion resistance | ISO 10582 | **Type 1** |
| | Dimensional stability | ISO 23999 | **Pass (≤ 0.25%)** |
| | Acoustic impact noise reduction | ISO 140-8 Improved Impact Sound Insulation | **ΔLw = 7 dB** |
| | Indentation - residual | ISO 24343-1 | **Pass (≤ 0.1 mm) Avg result 0.06mm** |
| | Castor chair continuous use | ISO 4918 | **Pass** |
| | | Underfloor heating | **Suitable. Max 27°C** |
| DS | Slip resistance[2] | AS/NZS 4586:2013 | **See separate table** |
| | Adhesive | General use: | **Karndean Mega-Bond** |
| | | High temperature: | **Two-part chemical cure adhesive or,** |
| | | | **One-part modified silane heat and moisture resistant adhesive** |
| floorscore | Environmental | Floorscore SCS-EC10.3-2014 v4.0 | **Certified** |
| SGS | | ISO 14001 / ISO 9001 | **Manufactured in certified facilities** |
| ResiLoop FOUNDING MEMBER | Partnerships | ResiLoop Founding Member | |
| | Recycling | | **Suitable** |

[1] Subject to terms. Please see our website.

[2] Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

Please verify the current certification status with your Business Manager

| Plank/Tile | Size (mm) | Size (in) | Box qty ($m^2$) | Box qty (pieces) | Slip Resistance |
|---|---|---|---|---|---|
| Plank | 1500.0 x 230.0 | 59.06 x 9.06 | 2.07 | 6 | R10, P3 |