

iD Comfort 19

14 modern designs

Acoustic comfort 19dB

Suitable for high traffic
areas

Easy glue-down
installation

Superior durability

WWW.TARKETT.COM.AU

LUXURY VINYL TILES

 **Tarkett**

iD Comfort 19

Technical Datasheet

Classification	Standards	iD Comfort 19
Product Type	EN ISO 10582	Heterogeneous poly (vinyl chloride) floorcovering
Classification	EN ISO 10874	Domestic: 23 Commercial: 33 Industrial: 42
Technical Characteristics	Standards	iD Comfort 19
Total thickness	EN ISO 24346	5.0mm
Wear layer thickness	EN ISO 24340	0.55mm
Total weight	EN ISO 23997	7190 g/m ²
Wear Layer Binder content	EN ISO 10582	Type I
Surface treatment		PUR
Bevelled edges		Yes
Installation method		Glue-Down
Technical Performances	Standards	iD Comfort 19
Dimensional stability	EN ISO 23999	≤ 0.10%
Reaction to fire	EN 13501-1	Critical radiant flux 9.1 kW/m ² Smoke 172%.min
Residual indentation	EN ISO 24343-1	≤ 0.10 mm
Furniture leg	EN 424	No damage
Castor chair	EN ISO 4918	No damage
Impact sound reduction	EN ISO 717/2	ΔLw 19dB
AAAC Rating	6577-1.1R REV B	6 Star
Thermal resistance	EN ISO 10456	0.04 m ² ·K/W
Colour fastness to light	EN ISO 105-B02 (method 3 ^o)	≥ 6
Chemical resistance	EN ISO 26987	High Resistance
Slip resistance	DIN 51130/EN 13893 AS 4586	P3
Sustainability Performances	Standards	iD Comfort 19
Phthalate		Not Detected
Total VOC emissions	EN 16516	Gold (≤ 100 µg / m ³)
Dimensions	Standards	iD Comfort 19
Tiles		457 x 914.4mm - 6 tiles/box = 2.51m ²
Planks		229 x 1219mm - 8 planks/box = 2.23m ²

The above information is subject to modification for the benefit of further improvement. (05/25). Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please note the the products in the photos are installed for creative purposes and not according to technical specifications.

